




CMIBF-2282X80-1

Cavity Filter

Electrical Specifications

Parameters	Specifications
Frequency	2242~2322MHz
Insertion Loss	≤0.5dB
VSWR	≤1.5:1
Rejection	≥40dB @1202~1575MHz ≥30dB @1575~2000MHz ≥25dB @2492~2600MHz ≥50dB @4564~6500MHz
Port Connectors	Pin \varnothing .02"x 0.079
Impedance	50 Ω
Power	150W
Operating Temperature	-55°C ~ +85°C
Surface Finish	Silver
Dimensions	See Attached Drawing (Dimensions are in inches [mm])

Outline Drawing



CALL OUR SALES DEPARTMENT FOR MORE INFORMATION OR VARIATIONS OF THIS PRODUCT.

Corry Micronics, Inc. One Plastics Rd. - Corry, PA 16407
(724) 940-7556 ext. 138 Fax (724) 940-7707 www.cormic.com

Corry Micronics Inc. herein referred to CMI, believes this information to be accurate, but makes no warranties, expressed or implied as to the accuracy of this document. CMI assumes no liability for any injury, loss, damage, direct or consequential arising from the use of our products. User assumes all risk whatsoever in connection with its intended use. CMI also reserves the right to change this document without notice. 05/29/2018