




CORRY MICRONICS, INC PRODUCT SPECIFICATION

CMIBF-9000X1000-1 Cavity Filter

Electrical Specifications

Parameters	Specifications
Frequency Range	8500~9500MHz
Insertion Loss	≤1.0dB
VSWR	≤1.3:1
Rejection	≥60dB@1000~3000MHz ≥50dB@3000~7000MHz ≥60dB@17000~19000MHz
Input Power	10W
Port Connectors	Pin Ø0.02"x0.08" [Ø0.5mm x2mm]
Impedance	50 Ω
Operating Temp.	-30°C~+70°C
Surface Finish	Silver
Dimensions	See Attached Drawing (Dimensions are in inches[mm])

Outline Drawing



CALL OUR SALES DEPARTMENT FOR MORE INFORMATION OR VARIATIONS OF THIS PRODUCT.

Corry Micronics, Inc. One Plastics Rd. - Corry, PA 16407
(724) 940-7556 ext. 138 Fax (724) 940-7707 www.cormic.com

Corry Micronics Inc. herein referred to CMI, believes this information to be accurate, but makes no warranties, expressed or implied as to the accuracy of this document. CMI assumes no liability for any injury, loss, damage, direct or consequential arising from the use of our products. User assumes all risk whatsoever in connection with its intended use. CMI also reserves the right to change this document without notice. 06/25/2018