



CORRY MICRONICS, INC PRODUCT SPECIFICATION

CMIPS-0912B6M

6 Bit Dispersive Phase Shifter Module

Specifications

Technical specification:

Parameters	Specifications (6 pcs in one package)
Frequency Range	0.9~1.2GHz
Insertion Loss	≤ 2.0 dB
VSWR	≤1.5: 1
Control Bit	6 bit (basic phase shift degrees: 5.625°, 11.25°, 22.5°, 45°, 90°, 180°)@1.05GHz (Center Frequency)
Phase Shift Flatness	≤±4°@1.05GHz (Center Frequency)
Amplitude variation	≤±0.3dB (caused by phase change)
Amplitude unbalance	≤±0.3dB (amplitude diff. between different phase shifter)
Phase unbalance	≤±3° (phase diff. between different phase shifter)
Power handling	≥550W peak power, pulse bandwidth 32us; ≥10W average power
Surface Finish	Natural color conductive oxidation

Power control:

1. Truth table: 6 bit TTL control (0: TTL low logic, 1: TTL high logic)
2. Power supply: +5V/400mA, -28V/50mA

Y1	Y2	Y3	Y4	Y5	Y6	Phase shift Reference
0	0	0	0	0	0	0°
1	0	0	0	0	0	-5.625°
0	1	0	0	0	0	-11.25°
0	0	1	0	0	0	-22.5°
0	0	0	1	0	0	-45°
0	0	0	0	1	0	-90°
0	0	0	0	0	1	-180°
						...
1	1	1	1	1	1	5.625°

CALL OUR SALES DEPARTMENT FOR MORE INFORMATION OR VARIATIONS OF THIS PRODUCT.

Corry Micronics, Inc. One Plastics Rd. - Corry, PA 16407
(724) 940-7556 ext. 138 Fax (724) 940-7707 www.cormic.com

Corry Micronics, Inc. herein referred to as CMI, believes this information to be accurate, but makes no warranties, expressed or implied as to the accuracy of this document. CMI assumes no liability for any injury, loss, damage, direct or consequential arising from the use of our products. User assumes all risk whatsoever in connection with its intended use. CMI also reserves the right to change this document without notice. 6/21/2016



CORRY MICRONICS, INC PRODUCT SPECIFICATION

Mechanical specifications:


1. RF connector: SMA-F;
2. Surface Finish: Natural color conductive oxidation
3. Power control connector: J30J-51ZKP, Pin definition listed as below

Pin	1	2	3	4	5	6	7	8	9	10
Definition	Y1-1	Y2-1	Y3-1	Y4-1	Y5-1	Y6-1	Y1-2	Y2-2	Y3-2	Y4-2
Pin	11	12	13	14	15	16	17	18	19	20
Definition	Y5-2	Y6-2	Y1-3	Y2-3	Y3-3	Y4-3	Y5-3	Y6-3	Y1-4	Y2-4
Pin	21	22	23	24	25	26	27	28	29	30
Definition	Y3-4	Y4-4	Y5-4	Y6-4	Y1-5	Y2-5	Y3-5	Y4-5	Y5-5	Y6-5
Pin	31	32	33	34	35	36	37	38	39	40
Definition	Y1-6	Y2-6	Y3-6	Y4-6	Y5-6	Y6-6	+5V	+5V	+5V	+5V
Pin	41	42	43	44	45	46	47	48	49	50
Definition	+5V	+5V	-28V	-28V	-28V	-28V	-28V	-28V	GND	GND
Pin	51									
Definition	GND									

Environmental specification:

1. Operating temperature: -40°C~+70°C
2. Storage temperature: -55°C~+85°C

Outline Drawing:



CALL OUR SALES DEPARTMENT FOR MORE INFORMATION OR VARIATIONS OF THIS PRODUCT.

Corry Micronics, Inc. One Plastics Rd. - Corry, PA 16407
(724) 940-7556 ext. 138 Fax (724) 940-7707 www.cormic.com

Corry Micronics Inc. herein referred to as CMI, believes this information to be accurate, but makes no warranties, expressed or implied as to the accuracy of this document. CMI assumes no liability for any injury, loss, damage, direct or consequential arising from the use of our products. User assumes all risk whatsoever in connection with its intended use. CMI also reserves the right to change this document without notice. 5/21/2018