FPA-218

JEM ENGINEERING

Two-Port Flat Panel Antenna

DESCRIPTION

The FPA-218 is a vertically-polarized, flat panel antenna, which provides high-level performance in a unique design that allows it to fit where no other antennas are able.

The antenna can be mounted to either a wall or a ceiling.

Designed to minimize space while maximizing transmission or detection, this antenna is easy to install and provides exceptional coverage across an ultra-wide frequency range.

This system is excellent for ELINT/SIGINT requirements over a broad band.

The FPA-218 is the medium (13.8" square) version of the FPA-218-2. Additionally, the FPA-218-3 (24.6" x 22.4" x 1.15", 200 to 18000 MHz) is the large version, with a three-output system.



Two-Port Flat Panel Antenna

SPECIFICATIONS

ELECTRICAL		MECHANICAL	
Frequency Bands		Weight	3.2 lbs (1.44 kg)
J2:	260 MHz to 2.5 GHz	Dimensions	19.2" L x 14.2" W x 0.7" Thick
J1:	2.5 GHz to 18 GHz		(48.8 cm L x 36 cm W x 1.78 cm Thick)
VSWR	< 4.0 : 1 at 260 MHz to 2.5 GHz	Mounting	Nylon Mounting Plates
Return Loss	\leq -4.2 dB at 2.5 GHz to 18 GHz		Options for Wall or Ceiling Mounting
Polarization	Vertical, Linear	Finish (Default)	Harcell Texture ABS (White)
Pattern	Omni-Directional (Az)		
Connector	SMA Female	RELATED PRODUCTS	
	(Others Upon Request)	Small 2-Port Version	FPA-218-2 (260 MHz to 18 GHz)
			13.8" x 13.8" [35 cm x 35 cm]
ENVIRONMENTAL		Large 3-Port Version	FPA-218-3 (200 MHz to 18 GHz)
Operational Temp.	-31°F to +185°F (-35°C to +85°C)		24.6" x 22.4" [62.5 cm x 57 cm]