



CORRY MICRONICS, INC PRODUCT SPECIFICATION

LTE 869-894-45 LTE Power Amplifier 869-894 MHz 45 Watts

Functions

Num.	Description
1	ALC Point Control and Read
2	ALC on/Off Control and Read
3	PA Mute On/Off Control and Read
4	Digital Attenuator Control
5	Operating Temperature Monitor and Alarm
6	Output Power Monitor
7	Reverse Power Monitor and Alarm
8	DC Current Monitor and Alarm
9	Protected Against High Reflected Power

Environmental Specifications

Parameter	Specification
Max Base Plate Operating Temp.	0° to +85° C Shutdown @ 90° C
Relative Humidity	5% ~ 96 %
Atmospheric Pressure	70 kPa ~ 106 kPa
Cooling	Not provided, User Supplied

CALL OUR SALES DEPARTMENT FOR MORE INFORMATION OR VARIATIONS OF THIS PRODUCT.

Corry Micronics, Inc. One Plastics Rd. - Corry, PA 16407
(724) 940-7556 ext. 138 Fax (724) 940-7707 www.cormic.com

Corry Micronics Inc. herein referred to CMI, believes this information to be accurate, but makes no warranties, expressed or implied as to the accuracy of this document. CMI assumes no liability for any injury, loss, damage, direct or consequential arising from the use of our products. User assumes all risk whatsoever in connection with its intended use. CMI also reserves the right to change this document without notice. 12/14/2017

Electrical Specifications

Parameter	Specification
Frequency	869 – 894 MHz
Signal Type	LTE, PAR 9.8 dB @ 0.01%
Nominal Output Power	45 W
Nominal Gain	51 dB
ACLR	$\leq -45\text{dBc}$
EVM (Max)	$< 8\%$ @ Specified Output Power
Gain w/ ALC off +/- 1db	51 \pm 1.5 dB (Room Temperature/ Value of attenuator 8.5 dB) 51 \pm 2 dB (Low and High Temperature/ Value of attenuator 8.5 dB)
Input Return Loss	18 dB
Output Return Loss	18 dB
Tx ALC control range vs. Tx input level change, Min	16 dB (Nominal Input +/- 8 dB)
ALC Set Range	16 dB (46.5 ~ 31.5 dBm)
ALC Set Step	0.5 dB
ALC Control Accuracy	± 1 dB
Attenuator Set Range (ALC Off)	31 dB
Attenuator Set Step (ALC Off)	0.25 dB
Max Input Level, No Damage and Degradation	0 dBm (Adjust the attenuator to maintain output power)
Noise Figure (ALC Off)	≤ 10 dB
DC Power	+28V
Efficiency	$\geq 25\%$ @ 45 W
Output Load Mismatch Tolerance	Isolator Protected

CALL OUR SALES DEPARTMENT FOR MORE INFORMATION OR VARIATIONS OF THIS PRODUCT.

Corry Micronics, Inc. One Plastics Rd. - Corry, PA 16407
(724) 940-7556 ext. 138 Fax (724) 940-7707 www.cormic.com

Corry Micronics Inc. herein referred to CMI, believes this information to be accurate, but makes no warranties, expressed or implied as to the accuracy of this document. CMI assumes no liability for any injury, loss, damage, direct or consequential arising from the use of our products. User assumes all risk whatsoever in connection with its intended use. CMI also reserves the right to change this document without notice. 12/14/2017

Power Consumption when Muted	< 5 W
Forward Power Monitor	Range: 30 dB, 50 dBm ~ 21 dBm Resolution: 0.1 dBm Accuracy: ± 2 dB
Reverse Power Monitor	Range: 30 dB, 50 dBm ~ 21 dBm Resolution: 0.1 dBm Accuracy: ± 2 dB
DC Current Monitor	Range: 0 - 15 A Resolution: 0.1A Accuracy: ± 5 %
Temperature Monitor	Range: -40° C ~ +105° C Resolution: 1° C Accuracy: ± 3° C
RF Connectors	SMA Female
Power Connector	M3 Screw Terminal
Control Connector	4 Position 2.5 mm Pitch Header Mates With JST XHP-4
Dimensions	See Attached Drawing (Dimensions are in mm)

Control Pins

Pin Number	Description
1	GND
2	RS484_A
3	RS485_B
4	NC


CALL OUR SALES DEPARTMENT FOR MORE INFORMATION OR VARIATIONS OF THIS PRODUCT.

Corry Micronics, Inc. One Plastics Rd. - Corry, PA 16407

(724) 940-7556 ext. 138 Fax (724) 940-7707 www.cormic.com

Corry Micronics Inc. herein referred to CMI, believes this information to be accurate, but makes no warranties, expressed or implied as to the accuracy of this document. CMI assumes no liability for any injury, loss, damage, direct or consequential arising from the use of our products. User assumes all risk whatsoever in connection with its intended use. CMI also reserves the right to change this document without notice. 12/14/2017

Outline Drawing



CALL OUR SALES DEPARTMENT FOR MORE INFORMATION OR VARIATIONS OF THIS PRODUCT.

Corry Micronics, Inc. One Plastics Rd. - Corry, PA 16407
(724) 940-7556 ext. 138 Fax (724) 940-7707 www.cormic.com

Corry Micronics Inc. herein referred to CMI, believes this information to be accurate, but makes no warranties, expressed or implied as to the accuracy of this document. CMI assumes no liability for any injury, loss, damage, direct or consequential arising from the use of our products. User assumes all risk whatsoever in connection with its intended use. CMI also reserves the right to change this document without notice. 12/14/2017